



## DATA LOGGER SG-DL1000

### Communication accessories



Built-in web server, support LAN monitoring

Data storage for 12 months

Automatic network clock synchronization

RS485 interface for connecting inverters

Standard RJ45 Patch cable

Connection	Inverter: RS485 Router: RJ45
Access number	20pcs
Distances	1200m
Display	LED
Battery nominal voltage	48V
Input	
Voltage	Input: AC 90V - 250V 50/60Hz Output: DC 5V
Static energy consumption	1W
General	
Operating temperature	-25°C - 55°C
Humidity	10% - 95%
Protection	IP20
Dimension (L*W*H)	118* 78* 29mm

## WiFi Module SG-WIFI

### Communication accessories



Plug and play, fast and convenient

Preferable monitoring solution for residential use

Connection	TTL serial
Access number	802.11 b/g/n
Distances	100m
Settaggi	APP/WEB
Input	
Voltage	DC 5V
Static energy consumption	<1.6W
General	
Operating temperature	-25°C - 60°C
Humidity	10% - 90%
Protection	IP65
Dimension (L*W*H)	71.4* 71* 38mm

## LAN Module SG-LAN

### Communication accessories



Plug and play, fast and convenient.

Preferred monitoring solution for residential use.

Connection	TTL serial
Access number	LAN
Settings	Plug and Play
Input	
Voltage	DC 5V
Static power consumption	<1.6W
General	
Operating temperature	-25°C - 60°C
Humidity	10% - 90%
Protection	IP65
Size (L*W*H)	71.4* 71* 38mm

## Single Phase SG-D669

### Accessories

Single-phase meter 220V 5(80)A 2P

\* The meters may vary from those shown in the picture.



## Three Phase SG-T670

### Accessories

Three-phase meter 3\*230/400V 5(80)A

\* The meters may vary from those shown in the picture.

