



Efficiency	
Max. Efficiency	98.4%
Efficienza europe	98.0%
Input (FV)	
Max. input voltage	1100V
Max. PV configuration (STC)	150%
Rated input voltage	620V
Max. Input current	(2*30A)
Max short circuit current	(2*40A)
Starting input voltage	180V
MPPT operating voltage range	160V-1000V
Max. number of PV strings	4 (2/2)
No. of MPPTs	2
Outputs (network)	
Nominal AC active power	30000W
Max. AC apparent power	33000VA
Max. AC active power (PF=1)	33000W
Max. AC output current	3*50.2A
AC rated voltage	380V I 400V/415V, 3W+N+PE
AC voltage range (1)	260V-510V (Adjustable)
Nominal grid frequency	50Hz/ 60Hz
Network frequency range(2)	45Hz-55Hz/55Hz-65Hz (Adjustable)
THDI	<3%@Rated Power
DC injection	<0.5%@Rated Current
Power factor	>0.99 Rated power (Adjustable 0.8 LD-0.8 LG)
Protection	
DC switch	Yes
Anti-island protection	Yes
AC overcurrent protection	Yes
AC short circuit protection	Yes
DC reverse connection	Yes
Surge arrester	DCType III/ AC TypeIII
Insulation control	Yes
Leakage current protection	Yes
General	
Typology	Transformerless
Environmental protection grade	IP66
Nocturnal self-consumption	<1W
Cooling mode	Fan cooling
Operating temperature range	-250c-60°c
Relative humidity range	0-100%
Max. operating altitude	4000m
Noise (typical)	<50dB
Dimensions (W*H*D)	398mm*460mm*190mm
Weight	20Kg
HMI & COM	
Display	Wireless & APP+LED, LCD (Optional)
Communication	RS485, WiFi / GPRS / 4G / LAN (optional)
Certification	
Safety	IEC62109-1/2
Grid	IEC 61000-1/2/3/4, IEC 61727/62116, CEI 021
Warranty	5 /10 years (optional)

*The output voltage and frequency range may vary according to different grid codes.

*Specifications are subject to change without notice.