



## SG-WB44KW

### 44KW Charging Station

#### CHARACTERISTICS

It supports intelligent charging mode (automatic, timed, flat rate, quantitative charging mode), various payment methods, various communication interfaces, visual remote control and high safety performance, suitable for private parking lots, underground garages, shopping malls, hotels, public parking lots, etc.



|                                |                                                                                                                |
|--------------------------------|----------------------------------------------------------------------------------------------------------------|
| Voltage                        | 415V (trifase)                                                                                                 |
| Current & power                | 32A 44KW                                                                                                       |
| Charge interface               | Type 1 / Type 2 / GB / T                                                                                       |
| Frequency                      | 50Hz                                                                                                           |
| Standard                       | IEC 61851-1:2017 • IEC 62196-2:2016 • IEC 61851-1:2017 • IEC 62196-2:2016 • EN 61851-1:2001 • EN 61851-21:2001 |
| Environmental protection grade | IP65                                                                                                           |
| Operating temperature          | -25°C~+45°C                                                                                                    |
| Communication                  | Ethernet, 4G, Bluetooth, Wifi, other connection modes                                                          |
| User interface                 | LCD display (4.3 inch)                                                                                         |
| Cable material                 | TPE or TPU                                                                                                     |

**Compatible with stand SG-S12T44**

